#### Prospects for reactor monitoring with noble liquid detectors

Jingke Xu, for the LLNL noble liquid group

Applied Antineutrino Physics, Livermore, CA

Oct 11, 2018





#### LLNL-PRES-759437

This work was performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344. Lawrence Livermore National Security, LLC

### Reactor monitoring with antineutrinos

- Reactor operations may be monitored with antineutrino signals from the reactor
  - Direct information from the core
  - Unshieldable, can not be tampered
  - Non-intrusive monitoring
  - Sensitive to fuel cycle evolution
- Inverse Beta Decay (IBD) is widely used in reactor antineutrino detections
  - SONGS
  - PANDA
  - Chandler
  - WATCHMAN
  - ...



The San Onofre Nuclear Generating Station (SONGS) where reactor monitoring with a Gd-LS detector was demonstrated by LLNL and SNL.

### **Coherent Elastic Neutrino Nucleus Scattering**


CENNS is a supplemental approach to monitor reactors, possibly with compact detectors.

#### Advantages:

- High interaction cross section (N<sup>2</sup> enhancement)
- Small detection medium mass
- Small footprint

#### **Disadvantages:**

- Low signal energy at reactors (~1keV or lower)
- Possibly high background at ~1keV or lower
- Less neutrino energy information preserved



CENNS was first demonstrated by the COHERENT collaboration at the SNS using CsI targets. Science, 03 Aug 2017, DOI: 10.1126/science.aao0990

### **Dual-phase noble liquid TPCs**


Reactor CENNS signals are similar to WIMP dark matter search signals:

- Nuclear recoils at low energy
- Relatively low event rate

Dual-phase noble liquid TPCs have demonstrated high dark matter sensitivity

- Low radioactivity
- Single electron threshold
- Scalable


Reactor CENNS requires detection of charge signals only.



An illustration of signal generation in a dual-phase xenon TPC detector. For reactor CENNS events, only charge signals are expected.

### Scalability of noble liquid detectors


- Current IBD detectors suitable for reactor monitoring are ~1 ton or larger
- Ar/Xe/Ge detectors have comparable
  CENNS rates at ~200eV threshold
- A competitive reactor CENNS detector needs an mass of ~100-200 kg to have comparable signal rates
- Ar/Xe TPCs are scalable, and may compete with IBD



Estimated CENNS rate in different detector medium for a reactor of 1GW with 25m standoff

### Challenges in Ar/Xe TPCs for reactor CENNS

- Nuclear recoil signal at low energies not calibrated
  - <6 keV for Ar</p>
  - <1 keV for Xe</p>
- Background in this energy region not thoroughly studied
  - Radioactive background
  - Instrumental background
  - Cosmogenic background for near-surface operations




Low-energy spectrum measured by the DarkSide50 experiment -- Note the sharp background increase below 3 e-. Phys. Rev. Lett. 121, 081307 (2018)

#### **LLNL** nuclear recoil calibration - Ar

The LLNL noble liquid group carried out the Ar recoil calibration at the lowest energy reported up to data (6.7 keVr)

- Portable dual-phase Ar TPC
- 70 keV neutron beam
- End point measurement
- Field dependence studied




The measured charge yield of 6.7 keVr Ar recoils as a function of drift electric field, measured by LLNL. <u>Phys. Rev. Lett. 112, 171303(2014)</u>. The absolute charge scale may have a sizeable uncertainty

#### LLNL nuclear recoil calibration - Xe

We measured Xe recoils down to ~1 keVr with the best demonstrated accuracy

- Dedicated dual-phase Xe
  TPC detector
- DD neutrons (2.4 MeV)
- Backing spectrometry

Lower energy Xe recoil calibrations underway.




# Radioactive background in Ar TPCs

Reactor CENNS signals in Ar TPCs with atmospheric argon will be overwhelmed by <sup>39</sup>Ar decay

- Cosmogenic <sup>40</sup>Ar(n, 2n)<sup>39</sup>Ar
- High rate ~1 Bq/kg

Argon from some underground sources may have drastically lower <sup>39</sup>Ar concentration

- Xu, et al, <u>Astroparticle Physics 66, 53-60</u>
- DarkSide50, <u>Physical Review D 93 (8), 081101</u>




Estimated reactor CENNS rate in comparison with that of background (LLNL). <u>IEEE Trans.Nucl.Sci. 51 (2004)</u> 2151-2155

## Instrumental background in Xe TPCs

Xe TPCs have demonstrated 1,000 times lower radioactivity than Ar TPCs due to a) the low intrinsic radioactivity and b) high self-attenuation power.

Xe TPCs observed high instrumental e- background rates

- Impurity-related
- Unextracted electrons
- Photoionization electrons
- Metal surface emissions



Observed electron background in the LUX dark matter detector over an extended period of 0.5s. APS April Meeting 2016 Volume 61, Number 6, B16.00005

## Reactor CENNS with noble liquid TPCs

- ~100-200 kg of Ar/Xe dual-phase TPC
  - Compact footprint (~1 m²)
  - Low background rate with sufficient shielding
  - Suitable for surface operation
  - ~2-3 e- threshold
- High enough CENNS event rate
  - ~1000 cpd for 1 GWt thermal power at 25 m stand off
  - Respond to reactor operation interruptions within hours
  - Sensitive to fuel cycle evolution